



Your **in**house Laundry Partner

JLA 16, 22, 35, 40 and 50

Rigid Mount, Fast Speed Spin Washers



JLA 16

JLA 22

JLA 35

JLA 40

JLA 50

THE PROFESSIONALS CHOICE

SPECIFICATIONS

| Details | Units | JLA 16 | JLA 22 | JLA 35 | JLA 40 | JLA 50 |
|------------------------------|-------------------|-------------|-------------|-------------|-----------|-----------|
| Capacity | Kg(lb) | 7.3(16) | 9.5(22) | 16.5(35) | 18(40) | 23.5(50) |
| Height | mm | 1014 | 1014 | 1175 | 1175 | 1355 |
| Width | mm | 660 | 660 | 780 | 780 | 860 |
| Depth | mm | 800 | 900 | 1000 | 998 | 1050 |
| Net Weight | Kg | 181 | 178 | 298 | 308 | 383 |
| Drum Volume | m ³ /l | 0.073/73 | 0.095/95 | 0.165/165 | 0.181/181 | 0.234/234 |
| G.Force | Gs | 145 | 145 | 14.5 | 165 | 165 |
| Door Opening | Ø mm | 300 | 300 | 300 | 400 | 400 |
| Fixing Down | Bolt | Bolt | Bolt | Bolt | Bolt | Bolt |
| Electrics - 9KW Heater (1ph) | Volt/ph/Amp | 240/1/45(s) | 240/1/45 | 240/1/45 | - | - |
| Electrics - 6KW Heater | Volt/ph/Amp | 240/1/32 | 240/1/32 | 240/1/32 | - | - |
| Electrics - Steam Heated | Volt/ph/Amp | 240/1/10 | 240/1/10 | 240/1/16 | 240/1/10 | - |
| Electrics - 12KW Heater | Volt/ph/Amp | - | 415/3/32(s) | 415/3/32(s) | 415/3/32 | - |
| Electrics - 9KW Heater (3ph) | Volt/ph/Amp | 415/3/20 | 415/3/20 | - | - | - |
| Electrics - 18KW Heater | Volt/ph/Amp | - | - | 415/3/45 | 415/3/32 | 415/3/45 |
| Electrics - Steam Heated | Volt/ph/Amp | - | - | - | 240/1/16 | 240/1/16 |
| No. of Water Connections | cold/hot | 2/1 | 2/1 | 2/1 | 2/1 | 2/1 |
| Connection Size | " BSP | ¾ | ¾ | ¾ | ¾ | ¾ |
| Drain Connection (Gravity) | Ø mm | 50 | 50 | 50 | 50 | 75 |
| Steam Rating | Kg(lb)/cycle | 7.5(16) | 10(22) | 16.5(35) | 18(40) | 23.5(50) |
| Size | " BSP | ¾ | ¾ | ¾ | ¾ | ¾ |

All specifications subject to change without notice

JLA 16, 22, 35, 40 and 50

Rigid Mount, Fast Speed Spin Washers

Machines in this range are ideal for contamination risk sites such as hospitals, care homes, veterinary surgeries and stables. They meet NHS Guideline HSG 95(18) and Category 5 of the latest Water Regulations and comply with the National Minimum Care Standards. All machines feature LCD displays for ease of programming and less user error.

Features

Built-in Type 'A' air gap

LCD display

Microprocessor controlled

Two sluice programmes

High build quality

Liquid soap injection control board

Benefits

Eliminates the risk of water contamination and fully approved for direct connection to mains water, resulting in lower installation costs.

Displaying individual cycles for ease of use - optimum programming, less user error.

Standard with customised wash cycles to suit individual needs.

Separate programmes for both thermal and chemical disinfection depending on type of fabric being processed. Enables all laundry including heat labile fabrics to be processed without handling foul or infected items.

Stainless steel cabinet and drum - clean and hygienic, robust and reliable.

Easy connection to auto-dosing pump system.

For further information call 0800 591903

JLA Limited Meadowcroft Lane, Ripponden, West Yorkshire HX6 4AJ

T 01422 822282 **F** 01422 824390 **email** info@jla.com

JLA Limited River Lodge, Lucan, County Dublin **T** 01 601 0525 **F** 01 628 1937