



Your inhouse Laundry Partner

JLA 16 Stack System



JLA 16 STACK SYSTEM

THE PROFESSIONALS CHOICE

P/WD16/09/07

SPECIFICATIONS

Details	Units	JLA 16 Stack System	
Capacity	Kg(lb)	7.5(16)	
Height	mm	2086	
Width	mm	686	
Depth	mm	920	
Depth (including open door)	mm	1590	
Net Weight - Gas/Elec	Kg	300	
		Washer	Dryer
Drum Volume	m ³ /l	0.073/73	0.21/210
G.Force - Low/High spin	Gs	74/296	-
Door Opening	ømm	300	492
* Electrics	Volt/ph/Amp	240/1/45(s) 9 kw Heater (1ph)***	240/1/13 Gas
* Electrics	Volt/ph/Amp	240/1/32 6 kw Heater **	415/3/16 Elec
* Electrics	Volt/ph/Amp	240/1/10 Steam Heated **	240/1/45 Elec 8.1 kw **
* Electrics	Volt/ph/Amp	415/3/20 9 kw Heater (3ph)**	240/1/32 Elec 5.4 **
No. of Water Connections	Cold/Hot	2/1	1
Water Connection Size	" BSP	3/4	3/4
Gas Rating	KW (Btu/hr)	-	11.7(40,000)
Connection Size	" BSP	-	3/8
Airflow	m ³ (ft ³)/min	-	6.51(230)
Exhaust ø	mm	-	100
Ventilation/Make Up	m ³	-	0.026(40)
Drain Connection (Gravity)***	ømm	50	-
Steam Rating	Kg/lb/cycle	7.5(16)	20.41(45)

* Each pocket must be protected by its own breaker but both pockets must have one common isolator

** Optional

*** Machines are supplied as standard with 2 drain connections at 80mm and 155mm high. These are maximum heights with the levelling feet in place. In extreme cases optional raising legs can be supplied which will increase the height by a further 75mm or 125mm respectively.

All specifications subject to change without notice



Your inhouse Laundry Partner

SAFE - Sensor Activated Fire Extinguishing system

SAFE is a unique system specially designed to eliminate serious fires which start in tumble dryers. Developed exclusively for JLA, the Sensor Activated Fire Extinguishing system combats blazes which are often caused by spontaneous combustion or small loads that are over-dried.

SAFE is fast and efficient. When a fire starts in a dryer drum, two sensors detect the change in temperature and activate a sophisticated water vapour mechanism.

The vapour douses flames within seconds and the drum rotates, exposing and soaking all laundry to ensure that the fire is completely extinguished. The entire process takes just three minutes and if the fire restarts for any reason, the vapour mechanism reactivates.

A great advantage of SAFE is that the risk of major damage to dryer and property and flooding to premises is eliminated.

JLA 16 Stack System

The JLA 16 Stack System comprises a 16lb capacity washer and a compatible dryer which fit in the space of a single machine, making it ideal for installations where space is at a premium. Microprocessor controlled pre-set programmes eliminate user error while auto dry cycles prevent energy wastage and cut down on ironing and finishing - therefore reducing costs.

The dryer is up to twice as fast as other dryers of the same size and a key feature of the machine is the unique JLA S.A.F.E. system.

Features

Washer

Built-in Type 'A' air gap

Microprocessor controlled

Information display

Free-standing

Two spin speeds

Two sluice programmes

High build quality

Liquid soap injection control board

Choice of two drain heights

Dryer

LCD display

Microprocessor Control

Large Lint Drawer

HSI Ignition

Large heavy duty door

Slanting rib system in drum

Cylinder

Axial air flow system

Reversing drum (special order)

Benefits

Eliminates the risk of water contamination and fully approved for direct connection to mains water, resulting in lower installation costs.

Standard with customised wash cycles to suit individual needs.

Displays cycle selected, operating temperature, minutes remaining to the end of cycle enabling more efficient use of staff time.

Lower installation costs. No bolting down required.

1,000rpm super spin reduces drying time by up to 30% - saves cost, increases throughput and eliminates need for separate hydro extractor. Standard spin speed for delicates prevents creasing and fabric damage.

Separate programmes for both thermal and chemical disinfection depending on type of fabric being processed. Enables all laundry including heat labile fabrics to be processed without handling foul or infected items.

Stainless steel cabinet and drum - clean and hygienic, robust and reliable.

Easy connection to auto-dosing pump system.

Usually no need for a raising plinth.

Displaying individual cycles for each use - optimum programming, less user error.

Simple one-touch operation with pre-programmed cycles. Tailor made cycles can also be stored. 'Clean Lint Filter' prompt for maximum efficiency. Self diagnostic error codes for easy fault finding. Auto dry cycles prevent energy wastage and cut down on ironing and finishing.

More efficient drying, easy to clean.

Fast Hot Surface Ignition reduces running costs.

Robust steel door with gasketless glass and high density, tamper-resistant seal for safety and long life. Easy loading of bulk items.

Prevents loads balling up by tumbling the load from the back of the basket to the front for the best drying results.

Stainless steel drum for durability and hygiene.

Giving maximum drying efficiency and fast results, reducing running costs over conventional air flow dryers.

No tangling and more even drying for larger items.

For further information call 0800 591903

JLA Limited Meadowcroft Lane, Ripponden, West Yorkshire HX6 4AJ

T 01422 822282 F 01422 824390 email info@jla.com

JLA Limited River Lodge, Lucan, County Dublin T 01 601 0525 F 01 628 1937



www.jla.com